



Simultaneously locate and remove water from live gas mains whilst recycling the gas back into the main, reducing excavations and impact on the consumer.

Water Extraction Mains - Tier 2

- Significantly reduces quantity of excavations required when compared to traditional methods.
- Accurately locate the source of ingress to enable permanent repair and avoid repeat visits.
- Optional unique closed-loop system to recycle the gas back into the main or service.
- Fully compatible with Synthocam3 live gas CCTV systems used by all UK gas networks, keeping investment cost to a minimum.



- Quickly locate source of ingress.
- Simultaneously remove water to reinstate supply.
- Reduce excavation and repeat visits.
- Improve customer satisfaction.

- Suitable for live gas use on metallic mains 12" to 18" diameter.
- Standard push distance up to 120m from a single excavation.
- Option to recycle gas back into the main, significantly reducing emissions to atmosphere.
- Connect to bowser system for handling larger volumes of water.
- For use on low pressure up to 75mbarg.



CONTACT OUR TEAM TODAY TO DISCUSS YOUR REQUIREMENTS

01423 816060 > info@synthotech.co.uk > www.synthotech.com

Milner Court, Hornbeam Square South, Hornbeam Park, Harrogate, HG2 8NB

©2016 Synthotech Ltd. All rights reserved to make changes to design and specification without prior notice or consent. E&OE

+44 (0) 1423 816 060

INNOVATIVE ENGINEERING

WWW.SYNTHOTECH.COM